

# FLASHLUBE COOLANT PREMIX

## FLASHLUBE PTY LTD

Chemwatch Hazard Alert Code: 3

Chemwatch: 5629-90  
Version No: 2.1  
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 16/11/2023  
Print Date: 07/11/2024  
S.GHS.U.S.A.EN.E

### SECTION 1 Identification

#### Product Identifier

Product name	FLASHLUBE COOLANT PREMIX
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	

#### Recommended use of the chemical and restrictions on use

Relevant identified uses	AUTOMOTIVE COOLANT PREMIX Use according to manufacturer's directions.
--------------------------	--

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	FLASHLUBE PTY LTD
Address	249-263 Sunshine Road Tottenham VIC 3012 Australia
Telephone	03 9325 9700 03 9325 9771
Fax	Not Available
Website	<a href="http://www.flashlube.com">www.flashlube.com</a>
Email	sales@flashlube.com.au

#### Emergency phone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	+1 855-237-5573
Other emergency telephone number(s)	+61 3 9573 3188


Once connected and if the message is not in your preferred language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Acute Toxicity (Oral) Category 4, Serious Eye Damage/Eye Irritation Category 2A, Reproductive Toxicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2
----------------	--

#### Label elements

Hazard pictogram(s)	
---------------------	--

Signal word	Warning
-------------	---------

#### Hazard statement(s)

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

**Hazard(s) not otherwise classified**

Not Applicable

**Precautionary statement(s) Prevention**

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P202	Do not handle until all safety precautions have been read and understood.

**Precautionary statement(s) Response**

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P330	Rinse mouth.

**Precautionary statement(s) Storage**

P405	Store locked up.
------	------------------

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
107-21-1	50	<u>ethylene glycol</u>
149-57-5	1.5	<u>2-ethylhexanoic acid</u>
1310-73-2	0.4	<u>sodium hydroxide</u>
29385-43-1	<0.2	<u>tolyltriazole</u>
3734-33-6	0.001	<u>denatonium benzoate</u>

**SECTION 4 First-aid measures****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>▶ Quickly remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> </ul>

**Most important symptoms and effects, both acute and delayed**

See Section 11

**Indication of any immediate medical attention and special treatment needed**

Continued...

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

- ▶ Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- ▶ Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- ▶ Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

## SECTION 5 Fire-fighting measures

### Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Special protective equipment and precautions for fire-fighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<p>carbon dioxide (CO<sub>2</sub>) nitrogen oxides (NO<sub>x</sub>) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.</p> <ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> <li>▶ Mists containing combustible materials may be explosive.</li> </ul> <p>Combustion products include:</p>

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<p>Slippery when spilt.</p> <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>
<b>Major Spills</b>	<p>Slippery when spilt. Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow clothing wet with material to stay in contact with skin</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> </ul>
----------------------	--

Continued...

	<ul style="list-style-type: none"> <li>▶ Avoid contact with moisture.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT use aluminium or galvanised containers</b></li> <li>▶ Polyethylene or polypropylene container.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid strong acids, bases.</li> </ul>

**SECTION 8 Exposure controls / personal protection****Control parameters****Occupational Exposure Limits (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	sodium hydroxide	Sodium hydroxide	2 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	sodium hydroxide	Sodium hydroxide	Not Available	Not Available	2 mg/m <sup>3</sup>	Not Available

Ingredient	Original IDLH	Revised IDLH
ethylene glycol	Not Available	Not Available
2-ethylhexanoic acid	Not Available	Not Available
sodium hydroxide	10 mg/m <sup>3</sup>	Not Available
tolyltriazole	Not Available	Not Available
denatonium benzoate	Not Available	Not Available

**Occupational Exposure Banding**

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
2-ethylhexanoic acid	E	≤ 0.1 ppm
tolyltriazole	E	≤ 0.01 mg/m <sup>3</sup>
denatonium benzoate	E	≤ 0.01 mg/m <sup>3</sup>

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

**Exposure controls**

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations.</p> <p>Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Type of Contaminant:</th> <th style="text-align: left;">Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> </tbody> </table>	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
Type of Contaminant:	Air Speed:								
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)								
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)								
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)								

	<p>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</p> <p>2.5-10 m/s (500-2000 f/min.)</p> <p>Within each range the appropriate value depends on:</p> <table border="1" data-bbox="384 275 1145 432"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only	
Lower end of the range	Upper end of the range											
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents											
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity											
3: Intermittent, low production.	3: High production, heavy use											
4: Large hood or large air mass in motion	4: Small hood-local control only											
<p><b>Individual protection measures, such as personal protective equipment</b></p>												
<p><b>Eye and face protection</b></p>	<ul style="list-style-type: none"> <li>▶ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.</li> <li>▶ Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.</li> <li>▶ Alternatively a gas mask may replace splash goggles and face shields.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>											
<p><b>Skin protection</b></p>	<p>See Hand protection below</p>											
<p><b>Hands/feet protection</b></p>	<ul style="list-style-type: none"> <li>▶ Elbow length PVC gloves</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>											
<p><b>Body protection</b></p>	<p>See Other protection below</p>											
<p><b>Other protection</b></p>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>											

#### Recommended material(s)

##### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Continued...

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

FLASHLUBE COOLANT PREMIX

Material	CPI
NEOPRENE	A
NITRILE	A
PVC	A
BUTYL	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE+PVC	C
PE	C
PE/EVAL/PE	C
PVA	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON/CHLOROBUTYL	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### Ansell Glove Selection

Glove — In order of recommendation
AlphaTec® Solvex® 37-185
AlphaTec® 58-008
TouchNTuff® 83-500
MICROFLEX® 93-260
AlphaTec® 38-612
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® 58-735
AlphaTec® 79-700
AlphaTec® Solvex® 37-675

The suggested gloves for use should be confirmed with the glove supplier.

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Green/Blue/ Red or yellow clear liquid; miscible with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	1.06-1.08
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	7.5-9.5	<b>Decomposition temperature (°C)</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Applicable	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Applicable	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Applicable	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available

Continued...

<b>Solubility in water</b>	Miscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available
<b>Heat of Combustion (kJ/g)</b>	Not Available	<b>Ignition Distance (cm)</b>	Not Available
<b>Flame Height (cm)</b>	Not Available	<b>Flame Duration (s)</b>	Not Available
<b>Enclosed Space Ignition Time Equivalent (s/m3)</b>	Not Available	<b>Enclosed Space Ignition Deflagration Density (g/m3)</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

### Information on toxicological effects

<b>Inhaled</b>	<p>There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal.</p> <p>Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow.</p>
<b>Ingestion</b>	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs.</p>
<b>Skin Contact</b>	<p>There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition</p> <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>
<b>Eye</b>	<p>There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.</p>
<b>Chronic</b>	<p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Exposure to ethylene glycol over a period of several weeks may cause throat irritation, mild headache and low backache. These may worsen with increasing concentration of the substance. They may progress to a burning sensation in the throat, a burning cough, and drowsiness.</p>

<b>FLASHLUBE COOLANT PREMIX</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>ethylene glycol</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	Eye (Rodent - rabbit): 0.012ppm/3D
	Oral (Rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 100mg/1H - Mild
		Eye (Rodent - rabbit): 1440mg/6H - Moderate
		Eye (Rodent - rabbit): 500mg/24H - Mild
		Eye (Rodent - rat): 0.012%/3D
		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Skin (Rodent - rabbit): 555mg - Mild	
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
<b>2-ethylhexanoic acid</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 1260 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 20mg - Severe
	Oral (Rat) LD50: 2043 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (Rodent - rabbit): 10mg/24H



		Skin (Rodent - rabbit): 450mg - Mild
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
sodium hydroxide	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 1350 mg/kg <sup>[2]</sup>	Eye (Primate - monkey): 1%/24H - Severe
	Oral (Rabbit) LD50; 325 mg/kg <sup>[1]</sup>	Eye (Rodent - rabbit): 1% - Severe
		Eye (Rodent - rabbit): 100mg
		Eye (Rodent - rabbit): 1mg/24H - Severe
		Eye (Rodent - rabbit): 1mg/30S - Severe
		Eye (Rodent - rabbit): 400ug - Mild
		Eye (Rodent - rabbit): 50ug/24H - Severe
		Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (Human): 0.15%/96H
		Skin (Human): 2%/24H - Mild
		Skin (Human): 2.50%/24H
	Skin (Rodent - rabbit): 500mg/24H - Severe	
	Skin: adverse effect observed (corrosive) <sup>[1]</sup>	
tolyltriazole	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (Rodent - rabbit): 10mg - Mild
	Inhalation (Rat) LC50: >0.433 mg/L4h <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
	Oral (Rat) LD50: 675 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
denatonium benzoate	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>
	Inhalation (Rat) LC50: 0.2 mg/l4h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Rabbit) LD50; 508 mg/kg <sup>[2]</sup>	

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

**ETHYLENE GLYCOL**

[Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Substance is reproductive effector in rats (birth defects). Mutagenic to rat cells.

For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow. Following absorption, it is distributed throughout the body. In humans, it is initially metabolized by alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and glyoxal. These breakdown products are oxidized to glyoxylate, which may be further metabolized to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate carbon dioxide, which is one of the major elimination products of ethylene glycol. In addition to exhaled carbon dioxide, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination is rapid and occurs within a few hours.

Respiratory effects: Respiratory system involvement occurs 12-24 hours after swallowing sufficient amounts of ethylene glycol. Symptoms include hyperventilation, shallow rapid breathing, and generalized swelling of the lungs with calcium oxalate deposits occasionally appearing in the lungs. Respiratory system involvement appears to be dose-dependent and occurs at the same time as cardiovascular changes. Later, there may be other changes compatible with adult respiratory distress syndrome (ARDS). Swelling of the lung can be a result of heart failure, ARDS, or aspiration of stomach contents. Symptoms related to acidosis such as fast or excessive breathing are frequently observed; however, major symptoms such as swelling of the lung and inflammation of the bronchi and lungs are relatively rare, and are usually seen only in extreme poisoning.

Cardiovascular effects: Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of ethylene glycol poisoning by swallowing, which is 12-24 hours after acute exposure. The symptoms of poisoning involving the heart include increased heart rate, heart enlargement and ventricular gallop. There may also be high or low blood pressure, which may progress to cardiogenic shock. In lethal cases, inflammation of the heart muscle has been observed at autopsy. Cardiovascular involvement appears to be rare and usually seen after swallowing higher doses of ethylene glycol. In summary, acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.

Gastrointestinal effects: Common early acute effects of swallowing ethylene glycol include nausea, vomiting with or without blood, heartburn and abdominal cramping and pain. One patient showed intermittent diarrhea and pain, and after surgery, deposition of oxalate crystals was shown to have occurred.

Musculoskeletal effects: Reported musculoskeletal effects in cases of acute ethylene glycol poisoning include diffuse muscle tenderness and pain, associated with high levels of creatinine in the blood, and jerks and contractions associated with low calcium.

Liver effects: Autopsies carried out on people who died following acute ethylene glycol poisoning showed deposition of calcium oxalate in the liver as well as hydropic and fatty degeneration and cell death (necrosis) of the liver.

Kidney effects: Adverse kidney effects are seen during the third stage of ethylene glycol poisoning, 2-3 days after acute exposure. Calcium oxalate crystals are deposited in the tubules and are seen in the urine. There may also be degeneration and death of tubule cells, and inflammation of the tubule interstitium. If untreated, the degree of kidney damage progresses and leads to blood and protein in the urine, decreased kidney function, reduction in urine output and ultimately, kidney failure. With adequate supportive therapy, kidney function can return to normal or near normal.

Metabolic effects: Metabolic changes can occur within 12 hours of exposure to ethylene glycol. There may be metabolic acidosis, caused by accumulation of glycolic acid in the blood and therefore a reduction in blood pH. The anion gap is increased, due to increased unmeasured anions (mainly glycolate).

Effects on the nervous system: Adverse reactions involving the nervous system are among the first symptoms to appear in humans after ethylene glycol is swallowed. These early effects are also the only symptoms caused by unmetabolised ethylene glycol. Together with metabolic effects (see above), they occur from 0.5-12 hours after exposure and are considered to be part of the first stage in ethylene glycol poisoning. Inco-ordination, slurred speech, confusion and sleepiness are common in the early stages, as are irritation, restlessness and disorientation. Later, there may be effects on cranial nerves (which may be reversible over many months). Swelling of the brain (cerebrum)



	<p>and crystal deposits of calcium oxalate in the walls of the small blood vessels of the brain were found at autopsy in people who died after acute ethylene glycol poisoning.</p> <p>Reproductive effects: Animal testing showed that ethylene glycol may affect fertility, survival of fetuses and the male reproductive organs.</p> <p>Effects on development: Animal studies indicate that birth defects may occur after exposure in pregnancy; there may also be reduction in foetal weight.</p> <p>Cancer: No studies are known regarding cancer effects in humans or animal, after skin exposure to ethylene glycol.</p> <p>Genetic toxicity: No human studies available, but animal testing results are consistently negative.</p>		
<b>2-ETHYLHEXANOIC ACID</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
<b>SODIUM HYDROXIDE</b>	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.		
<b>TOLYLTRIAZOLE</b>	<p>** Benzotriazoles Coalition Synthetic Organic Chemical Manufacturers Association December, 2001</p> <p>For benzotriazoles</p> <p>There are several indications that the effects of phenolic benzotriazoles described in the literature might be caused by endocrine disruption, e.g. reduced concentrations of testosterone, higher concentrations of CYP 450, or higher activity of ethoxyresorufin-O-deethylase (EROD-activity). As in these cases there are also indications for toxic effects on the liver reported, the effects might actually be only secondary effects. With the present knowledge it is not possible to attribute them unambiguously as endocrine adverse effects of an equivalent level of concern.</p> <p>Several benzotriazole UV stabilisers showed significant human aryl hydrocarbon receptor (AhR) ligand activity. The AhR has roles in regulating immunity, stem cell maintenance, and cellular differentiation. A study indicated that certain benzotriazole UV stabilisers have the potential to accumulate and exert potent physiological effects in humans, analogous to polycyclic aromatic hydrocarbons and dioxins, which are known stable and toxic ligands. The polycyclic aromatic hydrocarbon the polycyclic aromatic hydrocarbon, benzo[a]pyrene (BaP), a ligand for AhR, induces its own metabolism and bioactivation to a toxic metabolites.</p> <p>Benzotriazole is the core structure present within the phenolic benzotriazole class. In vitro metabolism with rat liver microsomes yielded formation of 5- and 4-hydroxybenzotriazole (1.6 and 0.32% of the amount added, respectively). Overall metabolism was low (&lt;5% of the total amount added). Oral acute studies in rats and mice yielded LD50 values that ranged from 560 to 909 mg/kg. Intraperitoneal LD50 values in mice and rats ranged from 400-1000 and 500-900 mg/kg, respectively. A mouse intravenous LD50 of 238 mg/kg was identified. Dermal LD50 values were =1000 mg/kg in rats and rabbits, and inhalation LC50 values in rats were 1.5 mg/L and 1.91 mg/L/3 hours). Subchronic and short-term studies showed that oral administration to mice produced minimal effects on body weight while dose-dependent decreases in body weight were observed in rats. Endocrine effects, normocytic anemia, and leukopenia were noted in rats dosed for 26 weeks. The TL0 was 109 mg/kg. No effects on deaths and no clinical symptoms were noted in mice or rats orally administered (in food) benzotriazole =78 weeks. Additionally, no dose-related effects on reproductive organs were noted in either sex. Neoplastic liver nodules were observed in male Fischer rats fed 12,100 ppm benzotriazole for 78 weeks. However, historic laboratory controls incidences varied from 0 to 11% so the treatment-related effects could not be determined. Brain tumors occurred in three males and one female rat. Incidence of endometrial stromal polyps was increased significantly in female rats fed 6700 ppm for 78 weeks (22%), but not in female rats fed 12,100 ppm (16%). Significant increase in alveolar/bronchiolar carcinomas (18%) was observed female B6C3F1 fed 11,700 ppm benzotriazole for 104 weeks. Comparatively, a similar increase was not observed in female mice fed 23,500 ppm benzotriazole for the same period of time (6% increase). Historical laboratory control incidences varied from 0 to 7%. Genotoxicity studies indicate that the compound was not mutagenic to S. typhimurium strains TA97, TA98, or TA100 in the presence or absence of S9, or Chinese hamster ovary cells. Benzotriazole was also not mutagenic to S. typhimurium strain TA1535 in the absence of S9, but was mutagenic in the presence of S9. Conflicting results were obtained for effects in S. typhimurium strains TA1537 and TA1538 and E. coli WP2 uvrA. It did not produce DNA damage in E. coli PQ37. In Chinese hamster ovary cells, benzotriazole induced chromosomal aberrations in the presence of S9 and sister chromatid exchange in the absence of S9. Benzotriazole was not genotoxic in the mouse micronucleus assay at 800 mg/kg. Benzotriazole was identified as a non-sensitizer in the guinea pig maximization test. Benzotriazole was identified as irritating to rabbit eyes and minimally irritating to rabbit and guinea pig skin</p> <p>For phenolic benzotriazoles</p> <p>Overall, oral exposure (either through gavage or in feed) of the tested chemicals to rats led to liver effects. Increased absolute and/or relative liver weights were observed in several studies. Body weight and body weight gain changes were observed after administration of several test substances. Histopathological changes (e.g., foci, hypertrophy, and cytoplasmic vacuolization) and altered liver enzyme content and activities were also noted after treatment with different phenolic benzotriazoles. Haematological effects (e.g., altered white and red blood cell counts, altered albumin levels, and packed cell volume) were observed. For those studies that calculated no observed adverse effect levels (NOAELs), the values ranged from &lt;0.5 to ~5685 mg/kg/day</p> <p><b>Reproductive and teratology effects:</b> The chemicals tested produced a variety of effects. Some chemicals were shown to affect reproductive organ weights, but no direct studies in reproduction and development were located.</p> <p><b>Genotoxicity</b> None of the tested compounds were identified as mutagenic in vitro in the absence or presence of a metabolic system (S9) or in vivo</p> <p>Chemical Information Review Document for Phenolic Benzotriazoles: Supporting Nomination for Toxicological Evaluation by the National Toxicology Program October 2011  <a href="https://ntp.niehs.nih.gov/ntp/noms/support_docs/phenolicbenzotriazoles_cird_oct2011_508.pdf">https://ntp.niehs.nih.gov/ntp/noms/support_docs/phenolicbenzotriazoles_cird_oct2011_508.pdf</a></p>		
<b>DENATONIUM BENZOATE</b>	<p>Somnolence, tremor, ataxia recorded.</p> <p>Most undiluted cationic surfactants satisfy the criteria for classification as Harmful (Xn) with R22 and as Irritant (Xi) for skin and eyes with R38 and R41.</p> <p>For quaternary ammonium compounds (QACs):</p> <p>Quaternary ammonium compounds are synthetically made surfactants. Studies show that its solubility, toxicity and irritation depend on chain length and bond type while effect on histamine depends on concentration. QACs may cause muscle paralysis with no brain involvement. There is a significant association between the development of asthma symptoms and the use of QACs as disinfectant.</p>		
<b>2-ETHYLHEXANOIC ACID &amp; SODIUM HYDROXIDE</b>	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
<b>2-ETHYLHEXANOIC ACID &amp; SODIUM HYDROXIDE &amp; DENATONIUM BENZOATE</b>	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.		
<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✗	<b>Reproductivity</b>	✓
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✓
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

FLASHLUBE COOLANT PREMIX	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
ethylene glycol	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	Not Available	Algae or other aquatic plants	6500-7500mg/l	1
	EC50	48h	Crustacea	>100mg/l	2
	LC50	96h	Fish	8050mg/L	4
	EC50	96h	Algae or other aquatic plants	6500-13000mg/l	1
2-ethylhexanoic acid	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	49.3mg/l	2
	EC50	48h	Crustacea	85.4mg/l	1
	LC50	96h	Fish	>100mg/l	2
	NOEC(ECx)	24h	Fish	14.424mg/L	4
EC50	96h	Algae or other aquatic plants	41mg/l	1	
sodium hydroxide	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	34.59-47.13mg/l	4
	EC50(ECx)	48h	Crustacea	34.59-47.13mg/l	4
LC50	96h	Fish	144-267mg/l	4	
tolyltriazole	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	29mg/l	2
	EC50	48h	Crustacea	35.4mg/l	Not Available
	LC50	96h	Fish	21.4mg/l	Not Available
EC50(ECx)	48h	Crustacea	35.4mg/l	Not Available	
denatonium benzoate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	EC50	48h	Crustacea	>500mg/l	2
	LC50	96h	Fish	>100mg/l	2
NOEC(ECx)	48h	Crustacea	50mg/l	2	
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
2-ethylhexanoic acid	LOW	LOW
sodium hydroxide	LOW	LOW

## Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene glycol	LOW (BCF = 200)
2-ethylhexanoic acid	LOW (LogKOW = 2.64)
sodium hydroxide	LOW (LogKOW = -3.8796)

## Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (Log KOC = 1)
2-ethylhexanoic acid	LOW (Log KOC = 24.06)
sodium hydroxide	LOW (Log KOC = 14.3)

## SECTION 13 Disposal considerations

### Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
-------------------------------------	---

## SECTION 14 Transport information

### Labels Required

<b>Marine Pollutant</b>	NO
-------------------------	----

**Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethylene glycol	Not Available
2-ethylhexanoic acid	Not Available
sodium hydroxide	Not Available
tolyltriazole	Not Available
denatonium benzoate	Not Available

#### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethylene glycol	Not Available
2-ethylhexanoic acid	Not Available
sodium hydroxide	Not Available
tolyltriazole	Not Available
denatonium benzoate	Not Available

## SECTION 15 Regulatory information

### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List  
 US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants  
 US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity  
 US - California Proposition 65 - Reproductive Toxicity  
 US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List  
 US - Massachusetts - Right To Know Listed Chemicals  
 US - New Jersey Right to Know Hazardous Substances  
 US - Pennsylvania - Hazardous Substance List  
 US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)  
 US Clean Air Act - Hazardous Air Pollutants  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US EPA Integrated Risk Information System (IRIS)  
 US EPCRA Section 313 Chemical List  
 US New York City Community Right-to-Know: List of Hazardous Substances  
 US NIOSH Recommended Exposure Limits (RELs)  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### 2-ethylhexanoic acid is found on the following regulatory lists

US - New Jersey Right to Know Hazardous Substances  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Section 4/12 (b) - Sunset Dates/Status

**sodium hydroxide is found on the following regulatory lists**

US - Massachusetts - Right To Know Listed Chemicals  
 US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Corrosives  
 US - New Jersey Right to Know Hazardous Substances  
 US - Pennsylvania - Hazardous Substance List  
 US CWA (Clean Water Act) - List of Hazardous Substances  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US New York City Community Right-to-Know: List of Hazardous Substances  
 US NIOSH Recommended Exposure Limits (RELs)  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1 (Spanish)  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**tolytriazole is found on the following regulatory lists**

US DOE Temporary Emergency Exposure Limits (TEELs)  
 US EPA Substance Registry Services (SRS) - 2020 CDR TSCA 4 TR  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**denatonium benzoate is found on the following regulatory lists**

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**Additional Regulatory Information**

Not Applicable

**Federal Regulations****Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312 hazard categories**

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	Yes
Reproductive toxicity	Yes
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

**US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)**

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylene glycol	5000	2270
sodium hydroxide	1000	454

**US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)**

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

CAS No	%[weight]	Name
107-21-1	50	ethylene glycol

*This information must be included in all SDSs that are copied and distributed for this material.*

**Additional Federal Regulatory Information**

Not Applicable

**State Regulations****US. California Proposition 65**

**WARNING:** This product can expose you to chemicals including **ethylene glycol**, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Additional State Regulatory Information**

Not Applicable

**National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylene glycol; 2-ethylhexanoic acid; sodium hydroxide; tolyltriazole; denatonium benzoate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

**SECTION 16 Other information**

<b>Revision Date</b>	16/11/2023
<b>Initial Date</b>	16/11/2023

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
  
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European Inventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory

▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.